

# Lock Bolts



**WARNINGS:**  
 Do not use a lock with a different seat style or size than the lug bolt being used on the wheel.  
 Do not use a lock shorter or longer than the lug bolt being used on the wheel.  
 Do not use more than one lock bolt per wheel.



## 60° Cone Seat Tuner Lock Bolts

A no-compromise design engineered to fit small diameter recesses in Tuner style wheels.

THREAD SIZE	OVERALL LENGTH	SHANK LENGTH	KEY HEX SIZE	PART NO.
M12x1.5	51.4mm 2.02"	22.4mm 0.88"	17mm	27192
M12x1.5	56.9mm 2.24"	29.6mm 1.16"	17mm	27191
M14x1.5	50.3mm 1.98"	24.0mm 0.95"	17mm	27200
M14x1.5	55.8mm 2.20"	28.6mm 1.13"	17mm	27201



## 60° Cone Seat Lock Bolts

THREAD SIZE	OVERALL LENGTH	SHANK LENGTH	KEY HEX SIZE	PART NO.
M12x1.25	47.1mm 1.86"	22.0mm 0.87"	17mm	27216 ▲
M12x1.25 black	47.1mm 1.86"	22.0mm 0.87"	17mm	27316 ▲
M12x1.25	54.5mm 2.15"	29.1mm 1.15"	19mm & 3/4	27169
M12x1.25	54.1mm 2.13"	25.6mm 1.01"	19mm & 3/4	27261 ▲
M12x1.25 black	54.1mm 2.13"	25.6mm 1.01"	19mm & 3/4	27361 ▲
M12x1.5	43.4mm 1.71"	18.2mm 0.72"	21mm & 13/16	27100
M12x1.5	47.4mm 1.86"	22.2mm 0.87"	17mm	27204
M12x1.5	50.7mm 2.00"	25.5mm 1.00"	17mm	27179 ▲
M12x1.5 black	50.7mm 2.00"	25.5mm 1.00"	17mm	27178 ▲
M12x1.5	56.9mm 2.24"	31.7mm 1.25"	17mm	27015
M12x1.5	61.5mm 2.42"	36.3mm 1.43"	21mm & 13/16	27111
M12x1.5	65.6mm 2.58"	40.5mm 1.59"	17mm	27013
M12x1.5	72.7mm 2.86"	49.2mm 1.94"	17mm	27014
M12x1.75	54.2mm 2.13"	28.9mm 1.14"	19mm & 3/4	27186
M14x1.25	51.7mm 2.04"	27.3mm 1.07"	17mm	27226 ▲
M14x1.25 black	51.7mm 2.04"	27.3mm 1.07"	17mm	27326 ▲
M14x1.5	51.4mm 2.02"	27.5mm 1.08"	17mm	27222
M14x1.5	52.9mm 2.08"	29.0mm 1.14"	17mm	27181
M14x1.5	54.9mm 2.16"	31.0mm 1.22"	19mm & 3/4	27000
M14x1.5	54.9mm 2.16"	31.0mm 1.22"	17mm	27205 ▲
M14x1.5 black	54.9mm 2.16"	31.0mm 1.22"	17mm	27305 ▲



## Radius Seat Lock Bolts

THREAD SIZE	SEAT RADIUS	OVERALL LENGTH	SHANK LENGTH	KEY HEX SIZE	PART NO.
M12x1.5	12mm	41.2mm 1.62"	20.6mm 0.81"	17mm	28176
M12x1.5	13mm	44.0mm 1.73"	23.3mm 0.92"	17mm	28175
M12x1.5	12mm	48.6mm 1.91"	27.9mm 1.10"	17mm	28172
M12x1.5	12mm	63.0mm 2.48"	39.9mm 1.57"	17mm	28023
M14x1.5	14mm	48.9mm 1.93"	27.0mm 1.06"	17mm	28174 ▲
M14x1.5 black	14mm	48.9mm 1.93"	27.0mm 1.06"	17mm	28374 ▲
M14x1.5	13mm	48.0mm 1.89"	26.7mm 1.05"	17mm	28018 ▲
M14x1.5 black	13mm	48.0mm 1.89"	26.7mm 1.05"	17mm	28318 ▲
M14x1.5	14mm	61.5mm 2.42"	28.2mm 1.11"	17mm	28020 ▲
M14x1.5 black	14mm	61.5mm 2.42"	28.2mm 1.11"	17mm	28320 ▲
M14x1.5	14mm	63.3mm 2.49"	35.4mm 1.39"	19mm & 3/4	28032 ▲
M14x1.5 black	14mm	63.3mm 2.49"	35.4mm 1.39"	19mm & 3/4	28332 ▲
M14x1.5	14mm	66.9mm 2.63"	45.0mm 1.77"	17mm	28017
M14x1.5 black	14mm	66.9mm 2.63"	45.0mm 1.77"	17mm	28317

Vehicles using lug bolts require either a cone seat or radius seat. The lock must have the same type of seat and size to properly fit the wheel.

Check the charts provided to be certain the thread size, seat type and size, and shank length are correct for the wheel being used. Match the chart information with a lug bolt being used on the wheel.

▲ This symbol denotes part numbers that are available in Wheel Installation Kits